

**Material Safety Data Sheet**

Impact Test Equipment Ltd  
[www.impact-test.co.uk](http://www.impact-test.co.uk) & [www.impact-test.com](http://www.impact-test.com)

**Impact Test Equipment Ltd.  
Building 21 Stevenston Ind. Est.  
Stevenston  
Ayrshire  
KA20 3LR**

T: 01294 602626

F: 01294 461168

E: [sales@impact-test.co.uk](mailto:sales@impact-test.co.uk)

Test Equipment Web Site

[www.impact-test.co.uk](http://www.impact-test.co.uk)

Test Sieves & Accessories Web Site

[www.impact-test.com](http://www.impact-test.com)

Section 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product name: LOGCO-LEASE P/ Mould Release Agent

1.2. Relevant identified uses of the substance or mixture and uses advised against

Use of substance / mixture: PC24: Lubricants, greases, release products.

1.3. Details of the supplier of the safety data sheet

Company name: Leeds Oil & Grease Co. Ltd

Cliffdale Road

Meanwood

Leeds

West Yorkshire

LS7 2JH

United Kingdom

Tel: +44 (0)11 3216 8822

Fax: +44 (0)11 3216 8833

Email: technical@logco.co.uk

1.4. Emergency telephone number

Emergency tel: +44 (0)113216 8822

(office hours only)

Section 2: Hazards identification

2.1. Classification of the substance or mixture

Classification under CLP: Asp. Tox. 1:H304

Most important adverse effects: May be fatal if swallowed and enters airways.

2.2. Label elements

Label elements:

Hazard statements: H304: May be fatal if swallowed and enters airways.

Hazard pictograms: GHS08: Health hazard



Signal words: Danger

Precautionary statements: P301+330+331: IF SWALLOWEDrinse mouth. Do NOT induce vomiting.

P305+351+338: IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

# SAFETY DATA SHEET

LOGCO-LEASE P

Page: 2

P405: Store locked up.

P501: Dispose of contents/container to licensed waste disposal site.

## 2.3. other hazards

**Other hazards:** Toxic if swallowed.

**PBT:** This product is not identified as a PBT/vPvB substance .

## Section 3: Composition/information on ingredients

### 3.2. Mixtures

#### Hazardous ingredients:

BASEOIL- UNSPECIFIED - DISTILLATES (PETROLEUM), HYDROTREATED LIGHT NAPHTHENIC - REACH registered number(s): 01-2119480375-34-0010

EINECS	CAS	PBT /WEL	CLP Classification	Percent
265-156-6	64742-53-6	-	-	>90%

## Section 4: First aid measures

### 4.1. Description of first aid measures

**Skin contact:** Remove all contaminated clothes and footwear immediately unless stuck to skin. Drench the affected skin with running water for 10 minutes or longer if substance is still on skin. Consult a doctor.

**Eye contact:** Bathe the eye with running water for 15 minutes. Transfer to hospital for specialist examination.

**Ingestion:** Do not induce vomiting. Wash out mouth with water. Give 1 cup of water to drink every 10 minutes. Transfer to hospital as soon as possible.

**Inhalation:** Remove casualty from exposure ensuring one's own safety whilst doing so. Move to fresh air in case of accidental inhalation of vapours. If conscious, ensure the casualty sits or lies down. If unconscious, check for breathing and apply artificial respiration if necessary. Consult a doctor.

### 4.2. Most important symptoms and effects, both acute and delayed

**Skin contact:** There may be mild irritation at the site of contact.

**Eye contact:** There may be irritation and redness.

**Ingestion:** There may be shortness of breath due to congestion of the lungs. May cause drowsiness.

**Inhalation:** There may be irritation of the throat with a feeling of tightness in the chest.

**Delayed / immediate effects:** Immediate effects can be expected after short-term exposure.

### 4.3. Indication of any immediate medical attention and special treatment needed

**Immediate / special treatment:** Immediate medical attention is required. Show this safety data sheet to the doctor in attendance .

[cont...]

# SAFETY DATA SHEET

LOGCO-LEASE P

Page: 3

---

## Section 5: Fire-fighting measures

---

### 5.1. Extinguishing media

---

**Extinguishing media:** Water fog. Carbon dioxide. Dry chemical powder. Alcohol or polymer foam. Use water spray to cool containers.

### 5.2. Special hazards arising from the substance or mixture

---

**Exposure hazards:** In combustion emits toxic fumes of carbon dioxide / carbon monoxide.

### 5.3. Advice for fire-fighters

---

**Advice for fire-fighters:** Wear self-contained breathing apparatus. Wear protective clothing to prevent contact with skin and eyes.

---

## Section 6: Accidental release measures

---

### 6.1. Personal precautions, protective equipment and emergency procedures

---

**Personal precautions:** Eliminate all sources of ignition. Turn leaking containers leak-side up to prevent the escape of liquid. Evacuate the area immediately. If outside keep bystanders upwind and away from danger point.

### 6.2. Environmental precautions

---

**Environmental precautions:** Do not discharge into drains or rivers. Contain the spillage using bunding.

### 6.3. Methods and material for containment and cleaning up

---

**Clean-up procedures:** Absorb into dry earth or sand. Mix with sand or vermiculite. Wash the spillage site with large amounts of water. Transfer to a closable, labelled salvage container for disposal by an appropriate method. Do not use equipment in clean-up procedure which may produce sparks.

### 6.4. Reference to other sections

---

**Reference to other sections:** Refer to section 8 of SOS.

---

## Section 7: Handling and storage

---

### 7.1. Precautions for safe handling

---

**Handling requirements:** Avoid the formation or spread of mists in the air. Ensure there is sufficient ventilation of the area.

### 7.2. Conditions for safe storage, including any incompatibilities

---

**Storage conditions:** Store in a cool, well ventilated area. Ensure storage room has retention walls. The floor of the storage room must be impermeable to prevent the escape of liquids. Keep container tightly closed.

**Suitable packaging:** Steel drums. Do not use aluminium containers. Do not use glass.

[cont...]

# SAFETY DATA SHEET

LOGCO-LEASE P

Page: 4

## 7.3. Specific end use(s)

Specific end use(s): No data available.

## Section 8: Exposure controls/personal protection

### 8.1. Control parameters

Workplace exposure limits: No data available.

### DNEUPNEC Values

#### Hazardous ingredients:

#### BASEOIL - UNSPECIFIED - DISTILLATES (PETROLEUM), HYDROTREATED LIGHT NAPHTHENIC

Type	Exposure	Value	Population	Effect
DNEL	Inhalation	5.4mg/m <sup>3</sup> /8h	-	-
PNEC	Oral-secondary poisoning	9.33 mg/kg	-	-

### 8.2. Exposure controls

**Engineering measures:** Ensure there is sufficient ventilation of the area. The floor of the storage room must be impermeable to prevent the escape of liquids. Ensure lighting and electrical equipment are not a source of ignition. Ensure storage room has retention walls.

**Respiratory protection:** Respiratory protection not required. Self-contained breathing apparatus must be available in case of emergency.

**Hand protection:** Nitrile gloves. Neoprene gloves.

**Eye protection:** Safety glasses with side-shields. Safety goggles.

**Skin protection:** Boots. Protective clothing. Protective clothing with elasticated cuffs and closed neck. Apron. Ensure safety shower is to hand.

**Environment tal:** The floor of the storage room must be impermeable to prevent the escape of liquids. Ensure storage room has retention walls. Storage should be placed inside a fully bunded area of sufficient size to contain the volume plus 10%. Prevent from entering in public sewers or the immediate environment.

## Section 9: Physical and chemical properties

### 9.1. Information on basic physical and chemical properties

**State:** Liquid

**Colour:** Gold-brown

**Odour:** Aromatic

**Evaporation rate:** Negligible

**Oxidising:** No data available.

**Solubility in water:** Insoluble

**Viscosity:** Non-viscous

**Kinematic viscosity:** 9-13c/ST

**Viscosity test method:** Kinematic viscosity in 10<sup>-6</sup> m<sup>2</sup>/s at 40°C (ISO 3104/3105)

[cont...]

# SAFETY DATA SHEET

LOGCO-LEASE P

Page: 5

Boiling point/range°C: 250 - 420

Melting point/range°C: Not applicable.

Flammability limits %: lower: No data available.

upper: No data available.

Flash point°C: 135

Part.coeff. n-octanol/water: No data available.

Autoflammability°C: >250

Vapour pressure: No data available.

Relative density: 0.881

pH: No data available.

VOE g/l: Not applicable.

## 9.2. Other information

Other information: Not applicable.

## Section 10: Stability and reactivity

### 10.1. Reactivity

Reactivity: Stable under recommended transport or storage conditions.

### 10.2. Chemical stability

Chemical stability: Stable under normal conditions.

### 10.3. Possibility of hazardous reactions

Hazardous reactions: Hazardous reactions will not occur under normal transport or storage conditions.

Decomposition may occur on exposure to conditions or materials listed below.

### 10.4. Conditions to avoid

Conditions to avoid: Heat.

### 10.5. Incompatible materials

Materials to avoid: Strong oxidising agents.

### 10.6. Hazardous decomposition products

Haz. decomp. products: In combustion emits toxic fumes of carbon dioxide/ carbon monoxide.

## Section 11: Toxicological information

### 11.1. Information on toxicological effects

Hazardous ingredients:

**BASEOIL- UNSPECIFIED - DISTILLATES (PETROLEUM), HYDROTREATED LIGHT NAPHTHENIC**

DERMAL	RAT	LD50	>5000	mg/kg
ORAL	RAT	LD50	>5000	mg/kg
VAPOURS	RAT	LC50	>5	mg/l

Relevant hazards for product:

Hazard	Route	Basis
--------	-------	-------

[cont...]

# SAFETY DATA SHEET

LOGCO-LEASE P

Page: 6

Aspiration hazard

Hazardous: calculated

## Symptoms / routes of exposure

**Skin contact:** There may be mild irritation at the site of contact.

**Eye contact:** There may be irritation and redness.

**Ingestion:** There may be shortness of breath due to congestion of the lungs. May cause drowsiness.

**Inhalation:** There may be irritation of the throat with a feeling of tightness in the chest.

**Delayed / immediate effects:** Immediate effects can be expected after short-term exposure.

**Other information:** Not applicable.

## Section 12: Ecological information

### 12.1. Toxicity

**Hazardous ingredients:**

#### BASEOIL - UNSPECIFIED - DISTILLATES (PETROLEUM), HYDROTREATED LIGHT NAPHTHENIC

ALGAE	48HIC50	100	mg/l
Daphnia magna	48H EC50	10,000	mg/l
FISH	96H LC50	100	mg/l

### 12.2. Persistence and degradability

**Persistence and degradability:** Biodegradable.

### 12.3. Bioaccumulative potential

**Bioaccumulative potential:** Slightly bioaccumulable.

### 12.4. Mobility in soil

**Mobility:** Insoluble in water. Floats on water. Readily absorbed into soil.

### 12.5. Results of PBT and vPvB assessment

**PBT identification:** This product is not identified as a PBT/vPvB substance.

### 12.6. other adverse effects

**Other adverse effects:** Negligible ecotoxicity.

## Section 13: Disposal considerations

### 13.1. Waste treatment methods

**Disposal operations:** Transfer to a suitable container and arrange for collection by specialised disposal company.

**Recovery operations:** Not applicable.

**Disposal of packaging:** Arrange for collection by specialised disposal company.

**NB:** The user's attention is drawn to the possible existence of regional or national regulations regarding disposal.

[cont...]



# SAFETY DATA SHEET

LOGCO-LEASE P

Page: 7

---

## Section 14: Transport information

---

**Transport class:** This product does not require a classification for transport.

---

## Section 15: Regulatory information

---

### 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

---

**Specific regulations:** Not applicable.

### 15.2. Chemical Safety Assessment

---

---

## Section 16: Other information

---

7

---

### Other information

---

**Other information:** This safety data sheet is prepared in accordance with Commission Regulation (EU) No 2015/830.

\* indicates text in the SOS which has changed since the last revision.

**Phrases used in s.2 and s.3:** H304: May be fatal if swallowed and enters airways.

**Legal disclaimer:** The above information is believed to be correct but does not purport to be all inclusive and shall be used only as a guide. This company shall not be held liable for any damage resulting from handling or from contact with the above product.